

LIGHTNING ROD POLE 50-80 FT.

SPECIFICATIONS

SHAFT

The shaft is fabricated from steel and is tapered, octagonal (50 ft.) or dodecagonal (80 ft.) in cross section. All shafts have a full length longitudinal submerged-arc weld ground smooth providing a uniform taper.

ANCHOR BASE

The anchor base is fabricated from structural steel conforming to G40.21-44W and is circumferentially welded inside and outside to the pole shaft.

HAND HOLE

All shafts are supplied with a 5"x12" hand hole ring opening and a weather proof cover. A ground lug is affixed inside the shaft accessible from the hand hole opening.


FINISH

The standard finish is 2C polyurethane or H.D.G..

NOTE

Consult the wind map for wind loading in your area.

Note:
All dimensions and constructions details are propriety to and property of CECO Poles.

		915 9th AVENUE S.E. CALGARY, ALBERTA T: 403 242 7475 F: 403 243 6190 EMAIL: info@nemalux.com	
DRAWN BY	*	TITLE	
DATE	*	STD. STEEL LIGHTNING POLE, 50-80 FT.	
APPR. BY	*	CUSTOMER/JOB	
SCALE	NTS	*	
QUANTITY	*	REV. NO.	DWG. NO.
		*	*